

# AUDIOLOGY TEST ROOMS

## AUDIO 1500

Slightly larger than its little sister the Audio 1000, the Audio 1500 has the same characteristics (both acoustically and level of equipment). This booth ensures an ideal patient environment for hearing tests, in cases where access is restricted. Given its dimensional characteristics, the Audio 1500 series is delivered as a kit. Delivery and installation are part of the turnkey service offered by Boët Stopson.

|                      |                                                                                                                                                                                                                                                                         |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions & weights | <ul style="list-style-type: none"><li>External dimensions : 1000 (L) x 1069 (P) x 2253 (H) mm</li><li>Internal dimensions : 894 (L) x 948 (P) x 2000 (H) mm</li><li>Net weight : 350 Kg / Gross weight : 400 kg</li></ul>                                               |
| Construction         | <ul style="list-style-type: none"><li>Constructed from 53 mm thick panels</li><li>Galvanised steel outer surface</li><li>Perforated galvanised steel inner surface designed to prevent particle migration and with high absorbency</li></ul>                            |
| Door                 | <ul style="list-style-type: none"><li>Clear passage : 604 mm (L) x 1680 mm (H)</li><li>Magnetic seals guarantee the acoustic sealing of the door as well as providing security for the users. The door can be supplied with a handle on the right or left.</li></ul>    |
| Acoustic window      | <ul style="list-style-type: none"><li>Double laminated glass 6mm thick</li><li>600 mm wide x 750 mm high glass installed in an Aluminium frame. The lower section has a frosted finish.</li></ul>                                                                       |
| Ventilation          | <ul style="list-style-type: none"><li>Ceiling panel includes a built-in 12 volt BS Cool-Air module for silent forced ventilation.</li></ul>                                                                                                                             |
| Connection panel     | <ul style="list-style-type: none"><li>Recessed connection panel is fully pre-wired :<ul style="list-style-type: none"><li>9 stereo 6,4 mm jacks</li><li>1 USB port</li></ul></li></ul>                                                                                  |
| Lighting             | <ul style="list-style-type: none"><li>3 maintenance free 12 volt LED lamps recessed into ceiling.</li></ul>                                                                                                                                                             |
| Electrics            | <ul style="list-style-type: none"><li>A 3m connecting cable equipped with a 12v socket for 220/240v mains connection.</li></ul>                                                                                                                                         |
| Finish               | <ul style="list-style-type: none"><li>Matt RAL 9010 polyester powder paint (interior/exterior)</li></ul>                                                                                                                                                                |
| Installation         | <ul style="list-style-type: none"><li>Supplied : mounted, equipped and operational.</li><li>Measurement equipment not provided.</li></ul>                                                                                                                               |
| Floor                | <ul style="list-style-type: none"><li>Anti-static mat, colour black.</li></ul>                                                                                                                                                                                          |
| Norm                 | <ul style="list-style-type: none"><li>The level of external noise/background noise <math>\leq 57</math> dB à 500 Hz (ISO 8253-1:2010), assuming the use of noise-cancelling headphones.</li></ul> <p><i>If further soundproofing is required please contact us.</i></p> |
| Options              | <ul style="list-style-type: none"><li>Anti-vibration mounts.</li><li>Variations for specific connection panel.</li></ul>                                                                                                                                                |

